



SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name: adhesive cleaner

1.2 Relevant identified uses of the substance or mixture and uses advised against

Application of the substance / the mixture Cleaning agent

1.3 Details of the supplier of the safety data sheet

Manufacturer/Supplier:

Prefa Aluminiumprodukte GmbH

Werkstraße 1

3182 Markt/Lilienfeld

Austria

T: +43 2762 502 0

Email: office.at@prefa.com

Further information obtainable from:

External:

Matthias Taxacher

E-mail: matthias.taxacher@innotec.at,

+43 5332 70800

www.innotec.at

1.4 Emergency telephone number:

+43 2762 502 0

Available during office hours:

Monday - Thursday: 07:00 - 12.00, 13:00 - 17:00 h

Friday: 07:00 - 13:00 h

Call the national emergency number!

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008

Flam. Liq. 2 H225 Highly flammable liquid and vapour.

Eye Irrit. 2 H319 Causes serious eye irritation.

STOT SE 3 H336 May cause drowsiness or dizziness.

Asp. Tox. 1 H304 May be fatal if swallowed and enters airways.

Additional information: For the wording of the hazard categories, see section 16.

2.2 Label elements

Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the GB CLP regulation.

(Contd. on page 2)



Trade name: adhesive cleaner

(Contd. of page 1)

Hazard pictograms



Signal word Danger

Hazard-determining components of labelling:

Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics
propan-2-ol
xylene, mixture of isomers

Hazard statements

H225 Highly flammable liquid and vapour.
H319 Causes serious eye irritation.
H336 May cause drowsiness or dizziness.
H304 May be fatal if swallowed and enters airways.

Precautionary statements

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P233 Keep container tightly closed.
P261 Avoid breathing mist/vapours/spray.
P280 Wear protective gloves / eye protection.
P301+P310 IF SWALLOWED: Immediately call a POISON CENTER/ doctor.
P331 Do NOT induce vomiting.
P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P403+P235 Store in a well-ventilated place. Keep cool.
P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

Additional information:

EUH066 Repeated exposure may cause skin dryness or cracking.

2.3 Other hazards

Results of PBT and vPvB assessment

PBT: No data available.

vPvB: No data available.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Description: Mixture of substances listed below with nonhazardous additions.

(Contd. on page 3)



Trade name: adhesive cleaner

(Contd. of page 2)

Dangerous components:

[% (w/w)]

CAS: 64742-48-9 EC number: 919-857-5 Index number: 649-327-00-6 Reg.nr.: 01-2119463258-33-XXXX	Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics	75 – 100%
	Flam. Liq. 3, H226 Asp. Tox. 1, H304 STOT SE 3, H336 EUH066	
CAS: 67-63-0 EINECS: 200-661-7 Index number: 603-117-00-0 Reg.nr.: 01-2119457558-25-XXXX	propan-2-ol	10 – 25%
	Flam. Liq. 2, H225 Eye Irrit. 2, H319; STOT SE 3, H336	
CAS: 1330-20-7 EINECS: 215-535-7 Index number: 601-022-00-9 Reg.nr.: 01-2119488216-32-XXXX	xylene, mixture of isomers	1 – 2.5%
	Flam. Liq. 3, H226 STOT RE 2, H373; Asp. Tox. 1, H304 Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319; STOT SE 3, H335 Aquatic Chronic 3, H412	

Additional information: For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

General information:

In case of discomfort or doubt, seek medical advice.

If unconscious, use a stable lateral position and do not administer anything through mouth.

After inhalation:

Supply fresh air. If required, provide artificial respiration. Keep patient warm. Consult doctor if symptoms persist.

In case of unconsciousness place patient stably in side position for transportation.

After skin contact:

Wash with plenty of soap and water.

Take off contaminated clothing and wash it before reuse.

Seek medical treatment in case of complaints.

After eye contact:

Rinse opened eye for several minutes under running water.

Remove contact lenses, if present and easy to do. Continue rinsing.

Seek medical treatment.

After swallowing:

Rinse mouth.

Do NOT induce vomiting.

Call a doctor immediately.

4.2 Most important symptoms and effects, both acute and delayed

No further relevant information available.

(Contd. on page 4)



Trade name: adhesive cleaner

(Contd. of page 3)

4.3 Indication of any immediate medical attention and special treatment needed

Depending on the condition of the patients, the doctor must assess the symptoms and the overall general condition.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing agents:

CO₂, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

For safety reasons unsuitable extinguishing agents: Water with full jet

5.2 Special hazards arising from the substance or mixture

Highly flammable liquid and vapour.

In case of fire, dangerous combustion gases or vapours may be generated.

Fumes can combine with air to form an explosive mixture.

5.3 Advice for firefighters

Protective equipment:

Wear self-contained respiratory protective device.

Wear fully protective suit.

Additional information

Cool endangered receptacles with water spray.

Collect contaminated fire fighting water separately. It must not enter the sewage system.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Restricted access to the affected area until cleaning work is completed.

Wear protective equipment. Keep unprotected persons away.

Ensure adequate ventilation

Avoid contact with skin and eyes.

Do not breathe vapour/spray.

Keep away from ignition sources.

6.2 Environmental precautions:

Do not allow to enter sewers/ surface or ground water.

Inform respective authorities in case of seepage into water course or sewage system.

6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding, inert material (sand, diatomite, acid binders, universal binders).

Dispose contaminated material as waste according to section 13.

Ensure adequate ventilation.

6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

(Contd. on page 5)



Trade name: adhesive cleaner

(Contd. of page 4)

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Keep receptacles tightly sealed.

Prevent formation of aerosols.

Avoid contact with skin and eyes.

Avoid breathing mist/vapours/spray.

Use personal protective equipment as required.

Observe protective measures and safety instructions.

Information about fire - and explosion protection:

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Protect against electrostatic charges.

Ground and bond container and receiving equipment.

Use explosion-proof apparatus / fittings and spark-proof tools.

Fumes can combine with air to form an explosive mixture.

7.2 Conditions for safe storage, including any incompatibilities

Storage:

Requirements to be met by storerooms and receptacles:

Store in a dry, cool, well-ventilated area.

Provide solvent resistant, sealed floor.

Store in accordance with local/regional/national/international regulations.

Information about storage in one common storage facility:

Store away from foodstuffs.

Store away from incompatible materials.

Further information about storage conditions:

Keep container tightly sealed.

Store only in the original receptacle.

Protect from heat and direct sunlight.

Recommended storage temperature: room temperature

Storage class: 3

7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Ingredients with limit values that require monitoring at the workplace:

CAS: 67-63-0 propan-2-ol

WEL	Short-term value: 1250 mg/m ³ , 500 ppm Long-term value: 999 mg/m ³ , 400 ppm
-----	--

CAS: 1330-20-7 xylene, mixture of isomers

WEL	Short-term value: 441 mg/m ³ , 100 ppm Long-term value: 220 mg/m ³ , 50 ppm Sk; BMGV
-----	--

(Contd. on page 6)

Safety data sheet
according to 1907/2006/EC



Printing date 27.06.2023

Version number 1.1 (replaces version 1.0)

Revision: 27.06.2023

Trade name: adhesive cleaner

(Contd. of page 5)

Regulatory information WEL: EH40/2020

DNELs		
CAS: 64742-48-9 Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics		
Oral	Long-term exposure - systemic effects	46 mg/kg bw/d (consumer)
Dermal	Long-term exposure - systemic effects	46 mg/kg bw/d (consumer)
		77 mg/kg bw/d (workers)
Inhalative	Long-term exposure - systemic effects	185 mg/m ³ (consumer)
		871 mg/m ³ (workers)
CAS: 67-63-0 propan-2-ol		
Oral	Long-term exposure - systemic effects	26 mg/kg bw/d (consumer)
	short-term exposure - systemic effects	51 mg/kg bw (consumer)
Dermal	Long-term exposure - systemic effects	319 mg/kg bw/d (consumer)
		888 mg/kg bw/d (workers)
Inhalative	Long-term exposure - systemic effects	89 mg/m ³ (consumer)
		500 mg/m ³ (workers)
		short-term exposure - systemic effects
		1,000 mg/m ³ (workers)
CAS: 1330-20-7 xylene, mixture of isomers		
Oral	Long-term exposure - systemic effects	12.5 mg/kg bw/d (consumer)
Dermal	Long-term exposure - systemic effects	125 mg/kg bw/d (consumer)
		212 mg/kg bw/d (workers)
Inhalative	Long-term exposure - systemic effects	65.3 mg/m ³ (consumer)
		221 mg/m ³ (workers)
	Long-term exposure - local effects	65.3 mg/m ³ (consumer)
		221 mg/m ³ (workers)
	short-term exposure - systemic effects	260 mg/m ³ (consumer)
		442 mg/m ³ (workers)
short-term exposure - local effects	260 mg/m ³ (consumer)	
		442 mg/m ³ (workers)
PNECs		
CAS: 1330-20-7 xylene, mixture of isomers		
fresh water		0.327 mg/l
sea water		0.327 mg/l
intermittent release (fresh water)		0.327 mg/l
STP		6.58 mg/l
sediment (fresh water)		12.46 mg/kg dw
sediment (sea water)		12.46 mg/kg dw

(Contd. on page 7)



Trade name: adhesive cleaner

(Contd. of page 6)

soil	2.31 mg/kg dw
------	---------------

Ingredients with biological limit values:

CAS: 1330-20-7 xylene, mixture of isomers

BMGV	650 mmol/mol creatinine Medium: urine Sampling time: post shift Parameter: methyl hippuric acid
------	--

Regulatory information BMGV: EH40/2011

Additional information: The lists valid during the making were used as basis.

8.2 Exposure controls

Appropriate engineering controls

No further data; see section 7.

Technical measures and the use of suitable working methods take priority over the use of personal protective equipment.

Individual protection measures, such as personal protective equipment

General protective and hygienic measures:

The usual precautionary measures are to be adhered to when handling chemicals.

Keep away from foodstuffs, beverages and feed.

Do not eat or drink while working.

Wash hands before breaks and at the end of work.

Avoid contact with the eyes and skin.

Immediately remove all soiled and contaminated clothing.

Do not inhale gases / fumes / aerosols.

Ensure good ventilation/exhaustion at the workplace.

Protective clothing needs to be selected specifically for the workplace, depending on concentrations and quantities of the hazardous substances handled. The chemical resistance of the protective equipment should be enquired at the respective supplier.

Respiratory protection:

Use suitable respiratory protective device in case of insufficient ventilation.

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

Hand protection



Protective gloves

EN 374

The glove material has to be impermeable and resistant to the product/ the substance/ the mixture.

Material of gloves

Nitrile rubber gloves; recommended material thickness: 0.35 mm, penetration time: > 480 min

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer.

(Contd. on page 8)



Trade name: adhesive cleaner

(Contd. of page 7)

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation.

Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

Eye/face protection



Tightly sealed goggles

EN 166

Body protection: Protective work clothing

Environmental exposure controls

Do not allow to enter sewers/ surface or ground water.

In case of seepage into the ground inform responsible authorities.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

General Information

Physical state	Fluid
Colour:	Clear
Odour:	Characteristic
Odour threshold:	No information available.
Melting point/freezing point:	No information available.
Boiling point or initial boiling point and boiling range	82 °C
Flammability	Highly flammable.
Lower and upper explosion limit	
Lower:	0.6 Vol %
Upper:	12 Vol %
Flash point:	13 °C
Auto-ignition temperature:	≥ 240 °C (CAS: 64742-48-9 Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics)
Decomposition temperature:	No information available.
pH	Not determined.
Viscosity:	
Kinematic viscosity	No information available.
Dynamic:	No information available.
Solubility	
water:	Not miscible or difficult to mix.
Partition coefficient n-octanol/water (log value)	

67-63-0	propan-2-ol	0,05 log Kow
---------	-------------	--------------

(Contd. on page 9)

Safety data sheet

according to 1907/2006/EC



Printing date 27.06.2023

Version number 1.1 (replaces version 1.0)

Revision: 27.06.2023

Trade name: **adhesive cleaner**

(Contd. of page 8)

1330-20-7	xylene, mixture of isomers	3,16 log Kow
Vapour pressure at 20 °C:		43 hPa
Density and/or relative density		
Density at 20 °C:		0.78 g/cm ³
Vapour density		No information available.
9.2 Other information		
Appearance:		
Form:		Fluid
Important information on protection of health and environment, and on safety.		
Ignition temperature:		Product is not selfigniting.
Explosive properties:		Product is not explosive. However, formation of explosive air/vapour mixtures are possible.
Solvent content:		
VOC (EC)		780 g/l
Change in condition		
Softening point/range		
Oxidising properties		No information available.
Evaporation rate		No information available.
Information with regard to physical hazard classes		
Explosives		void
Flammable gases		void
Aerosols		void
Oxidising gases		void
Gases under pressure		void
Flammable liquids		Highly flammable liquid and vapour.
Flammable solids		void
Self-reactive substances and mixtures		void
Pyrophoric liquids		void
Pyrophoric solids		void
Self-heating substances and mixtures		void
Substances and mixtures, which emit flammable gases in contact with water		void
Oxidising liquids		void
Oxidising solids		void
Organic peroxides		void
Corrosive to metals		void
Desensitised explosives		void

SECTION 10: Stability and reactivity

10.1 Reactivity No further relevant information available.

(Contd. on page 10)



Trade name: adhesive cleaner

(Contd. of page 9)

10.2 Chemical stability No decomposition if used and stored according to specifications.

10.3 Possibility of hazardous reactions Fumes can combine with air to form an explosive mixture.

10.4 Conditions to avoid

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

10.5 Incompatible materials: No further relevant information available.

10.6 Hazardous decomposition products:

No decomposition if used and stored according to specifications.

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity Based on available data, the classification criteria are not met.

LD/LC50 values relevant for classification:

CAS: 64742-48-9 Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics

Oral	LD50	> 5,000 mg/kg (rat)
Dermal	LD50	> 5,000 mg/kg (Rabbit)
Inhalative	LC50/4 h	> 5 mg/l (rat)

CAS: 67-63-0 propan-2-ol

Oral	LD50	5,840 mg/kg (rat)
Dermal	LD50	12,870 mg/kg (Rabbit)
Inhalative	LC50/4 h	30 mg/l (rat)

CAS: 1330-20-7 xylene, mixture of isomers

Oral	LD50	3,523 mg/kg (rat)
Dermal	LD50	1,100 mg/kg (Rabbit)

Skin corrosion/irritation Based on available data, the classification criteria are not met.

Serious eye damage/irritation Causes serious eye irritation.

Respiratory or skin sensitisation Based on available data, the classification criteria are not met.

Germ cell mutagenicity Based on available data, the classification criteria are not met.

Carcinogenicity Based on available data, the classification criteria are not met.

Reproductive toxicity Based on available data, the classification criteria are not met.

STOT-single exposure May cause drowsiness or dizziness.

STOT-repeated exposure Based on available data, the classification criteria are not met.

Aspiration hazard May be fatal if swallowed and enters airways.

11.2 Information on other hazards

Endocrine disrupting properties

None of the ingredients is listed.

(Contd. on page 11)



Trade name: adhesive cleaner

(Contd. of page 10)

* **SECTION 12: Ecological information**

12.1 Toxicity

Aquatic toxicity:

CAS: 64742-48-9 Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics

LL0 (96 h)	100 mg/l (fish) (Onchorhynchus mykiss)
LL50 (48 h)	> 1,000 mg/l (daphnia) (Daphnia magna)
LL50 (96 h)	> 1,000 mg/l (fish) (Onchorhynchus mykiss)

CAS: 67-63-0 propan-2-ol

EC50 (48 h)	> 13,000 mg/l (daphnia) (Daphnia magna)
LC50 (96 h)	9,640 mg/l (fish) (Pimephales promelas)
LC50 (24 h)	> 10,000 mg/l (daphnia) (Daphnia magna)
EC50 (72 h)	> 1,000 mg/l (algae) (Scenedesmus quadricauda)

CAS: 1330-20-7 xylene, mixture of isomers

EC50 (48 h)	1 mg/l (daphnia)
LC50 (96 h)	2.6 mg/l (fish)
NOEC (72 h)	0.44 mg/l (algae)
LC50 (72 h)	1.3 mg/l (algae)

12.2 Persistence and degradability

64742-48-9	Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics	80 % (28 d)
67-63-0	propan-2-ol	53 % (5 d)
1330-20-7	xylene, mixture of isomers	>60 % (28 d)

12.3 Bioaccumulative potential

67-63-0	propan-2-ol	0,05 log Kow
1330-20-7	xylene, mixture of isomers	3,16 log Kow

Bioconcentration factor (BCF)

CAS: 1330-20-7 xylene, mixture of isomers

BCF	25.9
-----	------

12.4 Mobility in soil No further relevant information available.

12.5 Results of PBT and vPvB assessment

PBT: No data available.

vPvB: No data available.

12.6 Endocrine disrupting properties

The product does not contain substances with endocrine disrupting properties.

12.7 Other adverse effects

Additional ecological information:

General notes:

Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water

(Contd. on page 12)



Trade name: adhesive cleaner

(Contd. of page 11)

Do not allow product to reach ground water, water course or sewage system.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system. Only dispose of product residues via authorised companies according to local legislation.

European waste catalogue

Notes: The European Waste Catalogue (EWC) classifies waste materials and categorises them according to what they are and how they were produced. This may cause other classifications. The final decision belongs to the last user.

14 06 03*	other solvents and solvent mixtures
HP3	Flammable
HP4	Irritant - skin irritation and eye damage
HP5	Specific Target Organ Toxicity (STOT)/Aspiration Toxicity

Uncleaned packaging:

Recommendation:

Dispose of packaging according to regulations on the disposal of packagings. Packagings that may not be cleansed are to be disposed of in the same manner as the product.

SECTION 14: Transport information

14.1 UN number or ID number

ADR/RID/ADN, IMDG, IATA

UN1993

14.2 UN proper shipping name

ADR/RID/ADN

1993 FLAMMABLE LIQUID, N.O.S. (ISOPROPANOL (ISOPROPYL ALCOHOL), Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics)

IMDG, IATA

FLAMMABLE LIQUID, N.O.S. (ISOPROPANOL (ISOPROPYL ALCOHOL), Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics)

14.3 Transport hazard class(es)

ADR/RID/ADN, IMDG, IATA



Class

3 Flammable liquids.

Label

3

14.4 Packing group

ADR/RID/ADN, IMDG, IATA

II

(Contd. on page 13)



Printing date 27.06.2023

Version number 1.1 (replaces version 1.0)

Revision: 27.06.2023

Trade name: adhesive cleaner

(Contd. of page 12)

14.5 Environmental hazards:	Not applicable.
14.6 Special precautions for user	Warning: Flammable liquids.
Hazard identification number (Kemler code):	33
EMS Number:	F-E, <u>S-E</u>
Stowage Category	B
14.7 Maritime transport in bulk according to IMO instruments	Not applicable.

Transport/Additional information:

ADR/RID/ADN

Limited quantities (LQ)	1L
Excepted quantities (EQ)	Code: E2 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml
Transport category	2
Tunnel restriction code	D/E

IMDG

Limited quantities (LQ)	1L
Excepted quantities (EQ)	Code: E2 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml
UN "Model Regulation":	UN 1993 FLAMMABLE LIQUID, N.O.S. (ISOPROPANOL (ISOPROPYL ALCOHOL), HYDROCARBONS, C9-C11, N-ALKANES, ISOALKANES, CYCLICS, <2% AROMATICS), 3, II

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Directive 2012/18/EU

Named dangerous substances - ANNEX I None of the ingredients is listed.

Seveso category P5c FLAMMABLE LIQUIDS

Qualifying quantity (tonnes) for the application of lower-tier requirements 5.000 t

Qualifying quantity (tonnes) for the application of upper-tier requirements 50.000 t

National regulations:

Information about limitation of use: Employment restrictions concerning juveniles must be observed.

15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

(Contd. on page 14)



Trade name: adhesive cleaner

(Contd. of page 13)

Relevant phrases

- H225 Highly flammable liquid and vapour.
- H226 Flammable liquid and vapour.
- H304 May be fatal if swallowed and enters airways.
- H312 Harmful in contact with skin.
- H315 Causes skin irritation.
- H319 Causes serious eye irritation.
- H332 Harmful if inhaled.
- H335 May cause respiratory irritation.
- H336 May cause drowsiness or dizziness.
- H373 May cause damage to organs through prolonged or repeated exposure.
- H412 Harmful to aquatic life with long lasting effects.
- EUH066 Repeated exposure may cause skin dryness or cracking.

Training hints

Regular training of staff involved in the transport of dangerous goods (in accordance with Chapter 1.3 ADR).

Before handling, storage or use for the first time, employees must be informed about the properties of the substance and about measures taken to ensure safety and environmental protection.

Department issuing SDS:

UmEnA GmbH

<http://umena.at>

Email: office@umena.at

Abbreviations and acronyms:

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

VOC: Volatile Organic Compounds (USA, EU)

DNEL: Derived No-Effect Level (UK REACH)

PNEC: Predicted No-Effect Concentration (UK REACH)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Flam. Liq. 2: Flammable liquids – Category 2

Flam. Liq. 3: Flammable liquids – Category 3

Acute Tox. 4: Acute toxicity – Category 4

Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Irrit. 2: Serious eye damage/eye irritation – Category 2

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2

Asp. Tox. 1: Aspiration hazard – Category 1

Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard – Category 3

*** Data compared to the previous version altered.**